




K-T3-A-80
Power:25W/30W
Diameter:80mm




Model	K-T3-A-80	K-T3-A-80
Product Photo		
Dimension(mm)		
Wattage	25W/30W	25W/30W
CCT	3000K/3500K/4000K	3000K/3500K/4000K
CRI	>90	>90
Beam Angle	15°/24°/36°/50°	15°/24°/36°/50°
Lumen	1735-2839LM	1735-2839LM
IP	IP 20	IP 20
Installation	1-phase track 2-phase track 3-phase track	1-phase track 2-phase track 3-phase track
Colour	Black/White	Black/White

Optical Accessories



Honeycomb Filter Stripped Glass Fabric Glass

T3 Series



Model	Power	LED voltage	LED Current	CRI	CCT	Beam Angle	LED Output	System output	Dimming Type
K-T3-A-8025	25W	36V	600mA	90	2700K	15°	2452lm	1924lm	ON-OFF
						24°	2452lm	1735lm	
						36°	2452lm	1747lm	
						50°	2452lm	1821lm	
	25W	36V	600mA	90	3000K	15°	2593lm	2035lm	ON-OFF
						24°	2593lm	1835lm	
						36°	2593lm	1848lm	
						50°	2593lm	1821lm	
	25W	36V	600mA	90	4000K	15°	2805lm	2201lm	ON-OFF
						24°	2805lm	1985lm	
						36°	2805lm	1999lm	
						50°	2805lm	1969lm	
K-T3-A-8030	30W	36V	700mA	90	2700K	15°	3022lm	2254lm	ON-OFF
						24°	3022lm	2545lm	
						36°	3022lm	2592lm	
						50°	3022lm	2593lm	
	30W	36V	700mA	90	3000K	15°	3144lm	2345lm	ON-OFF
						24°	3144lm	2648lm	
						36°	3144lm	2697lm	
						50°	3144lm	2698lm	
	30W	36V	700mA	90	4000K	15°	3192lm	2380lm	ON-OFF
						24°	3192lm	2688lm	
						36°	3192lm	2738lm	
						50°	3192lm	2739lm	

